



LaHabra Exterior Fast Patch



DESCRIPTION:

- Easy to Use
- Non-Shrinking patch for exterior use
- QUICK SETTING use within 15-20 minutes.

COVERAGE:

Varies with thickness, approximately 8-10 sq. ft. (0.75-1m²) per 40 lb. bag at 1/2 inch thickness.

CONTAINER:

- 40 lb (18.1 kg) net weight in a bag.
- Storage: Store off the ground and protect from rain and moisture.
- Shelf Life: 12 months if properly stored in the original container.

SURFACE PREPARATION:

- On stucco, masonry and concrete, apply only to surfaces that are sound, clean, dry, unpainted, and free of any residue which may affect the ability of LaHabra Exterior Fast Patch to bond to the surface.
- Do NOT apply Exterior Fast Patch in freezing weather or to frozen substrates.
- For additional options for surface preparation, contact Parex USA Technical Services Department.

MIXING:

- Material should be thoroughly mixed with cool, clean potable water to a trowelable consistency.

APPLICATION:

- Read the entire label before using this product
- The area to be patched should be dampened before patching. Small holes may be patched in one step. Large holes should be done in two steps with a scratch coat followed with a finish coat after the scratch coat takes up.
- Use Exterior Fast Patch immediately after mixing.
- Material should not be retempered.
- No other additives of any kind, such as portland cement, lime, rapid binders, antifreeze, accelerators, pigments, etc., should be added under any circumstance.

LIMITATIONS:

- Ambient and surface temperature must be 40°F (4.4°C) or higher during application and drying time. Protect from freezing for a period of not less than 24 hours after set has occurred. Provide supplemental heat and protection from precipitation as needed.
- Ambient and surface temperatures must not exceed 120°F (49°C) during and 24 hours after application.
- Avoid application in direct sunlight in hot weather.
- Always wear proper safety equipment, including particle mask, when mixing and/or applying this product.



Corporate Office

Parex USA, Inc.
4125 E. La Palma Ave., Suite 250
Anaheim, CA 92807
(866) 516-0061
Tech Support: (800) 226-2424

Facilities

Riverside, CA
French Camp, CA
Albuquerque, NM
Colorado Springs, CO
Anaheim, CA

North Hollywood, CA
San Antonio, TX
Redan, GA
Wilkes Barre, PA

